



Wavetrend's compact low gain Antenna with omni-directional coverage, designed for direct connection to an RX50 Solo Reader.



STUB ANTENNA AN50

Specifications

Environmental

| | |
|-----------------------|-----------------|
| Operating temperature | -40°C to + 85°C |
| Relative humidity | 40% to 95% |
| IP rating | IP65 |

Physical

| | |
|-----------------|----------------------|
| Length | 44.8mm |
| Weight | 8.5g |
| Colour | Matt black |
| Connection type | 50 Ohm SMA(M)RA Plug |

Electrical

| | |
|--------------|---------|
| Frequency | 433 MHz |
| Gain | 0 dBi |
| Polarization | Linear |
| Impedance | 50 Ohm |
| VSWR | <1.5:1 |

Read range

20m depending on installation and environment

To order or for further information



Wavetrend (Europe) Ltd. Barlavington Stud,
Barlavington, Petworth, West Sussex GU28 0LG, UK
www.wavetrend.net
T: + 44 (0) 330 223 2086/2085
E: sales@wavetrend.net

Any drawings, specifications, descriptive matter or advertising produced by Wavetrend Europe Limited, including the information contained within this flyer, are produced for the sole purpose of giving an approximate idea of the goods referred to in them and are subject to change without notice. They shall not form part of a contract nor have any contractual force.

Copyright © 2018 Wavetrend (Europe) Ltd | All Rights Reserved.